

XF 9.9 Team

Gloss Carbon / Red Carbon

MTB FULL-SUSPENSION / XF TEAM



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-71-41A, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305R1S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XTR SW-M9250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XTR RD-M9250, Shadow Plus Design
CRANKSET	SHIMANO XTR FC-M9200, 36T
CASSETTE	SHIMANO XTR CS-M9200, 12-speed, 10-51T
CHAIN	SHIMANO XTR CN-M9100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XTR M9200, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL900, 180mm
BRAKE REAR	SHIMANO XTR M9200, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL900, 160mm

WHEELS

WHEELSET FRONT	DT Swiss XRC 1200 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XRC 1200 SPLINE®, Carbon, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.35", ADDIX Speed
TIRE REAR	Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.35", ADDIX Speed

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X1, Carbon
SEATPOST LEVER	SRAM AXS POD, Dropper Post Lever
SEATPOST	SRAM Reverb AXS dropper post, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	42	42	42	42
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	645
STACK HEIGHT (MM)	583	593	602	611
REACH (MM)	439	460	478	496
SEAT TUBE ANGLE	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1153	1179	1200	1222
HANDLEBAR (MM)	760/60	760/60	760/80	760/80
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L390/T125	L390/T125	L440/T150	L440/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.