

XP 9.2

Gloss Purple

MTB HARDTAIL / XP



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-644, ICR, IPS, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SW-M6250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6250-SGS
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i25, Disc, 32H, Tubeless Ready
TIRE FRONT	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i25, Disc, 32H, Tubeless Ready
TIRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	13.5" (XS)	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	57	57	57	57	57
SEAT TUBE LENGTH (MM)	30	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	645
STACK HEIGHT (MM)	599	599	603	613	622
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	75,9°	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430	430
HEAD TUBE LENGTH (MM)	90	90	95	105	115
WHEELBASE (MM)	1127	1147	1169	1193	1217
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	170	170	170	175	175
SEATPOST (MM)	350	400	400	400	400