

XF 9.7 RC

Matte Carbon / Smoke Chrome

MTB FULL-SUSPENSION / XF RC



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-644S, ICR, IPS, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	S802-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XT SW-M8250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8250, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8220, 34T
CASSETTE	SHIMANO XT CS-M8200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO XT M8200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 160mm

WHEELS

WHEELSET FRONT	DT Swiss XM 1700 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XM 1700 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	42	42	42	42
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	645
STACK HEIGHT (MM)	583	593	602	611
REACH (MM)	439	460	478	496
SEAT TUBE ANGLE	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1153	1179	1200	1222
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.