

X-ROAD 6.3 GF

Gloss Grey / Black

ROAD & GRAVEL / GRAN FONDO



COMPUTER VISUALIZATION

SPECIFICATION

ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.5x14L, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO TIAGRA R-4720, 2-speed
SHIFTERS RIGHT	SHIMANO TIAGRA R-4720, 10-speed
FRONT DERAILEUR	SHIMANO TIAGRA FD-4700, Brazed-On Type
REAR DERAILEUR	SHIMANO TIAGRA RD-4700
CRANKSET	SHIMANO FC-RS400, 50-34T
CASSETTE	SHIMANO CS-HG500, 10-speed, 11-34T
CHAIN	KMC X10

BRAKING SYSTEM

BRAKE FRONT	SHIMANO TIAGRA R-4720, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 140mm
BRAKE REAR	SHIMANO TIAGRA R4720, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	STARS J22GT, Disc, 28H
TYRE FRONT	Schwalbe Lugano II, KevlarGuard, 32-622
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	STARS J22GT, Disc, 28H
TYRE REAR	Schwalbe Lugano II, KevlarGuard, 32-622
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal Gravel
SEAT POST	ONE Race, Alloy, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

GEOMETRY

FRAME SIZE	500mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
WHEEL SIZE	700c	700c	700c	700c	700c
BB DROP (MM)	70	70	70	70	70
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	523	530	540	570	590
STACK HEIGHT (MM)	549	558	569	606	616
REACH (MM)	368	367	371	384	401
SEAT TUBE ANGLE	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE	71,5°	71,5°	72°	73°	73°
REAR CENTER (MM)	414	414	414	414	414
HEAD TUBE LENGTH (MM)	125	135	145	180	190
WHEELBASE (MM)	949	992	990	1010	1029,8
STEM (MM)	80	80	90	100	110
HANDLEBAR (MM)	410	410	410	410	430
CRANKSET (MM)	170	170	170	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.