

XF 9.2 RC

Matte Carbon / White

MTB FULL-SUSPENSION / XF RC



SPECIFICATION

ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-220 R4, ZS44/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE FRONT	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 760mm, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
BB DROP (MM)	40	40	40	40
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
STACK HEIGHT (MM)	579	589	597	607
REACH (MM)	427	449	465	482
SEAT TUBE ANGLE	74,9°	74,7°	74,6°	74,5°
HEAD TUBE ANGLE	68°	68°	68°	68°
REAR CENTER (MM)	428	428	428	428
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1124	1149	1169	1189
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	125	125	150	150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.