

XF 9.6 DC

Matte Carbon / Grey

MTB FULL-SUSPENSION / XF TR



SPECIFICATION

ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

FRAMESET

FRAME	Carbon MTB DC SU-01.2, Advanced Down Country Geometry, Travel 130 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	RockShox PIKE Select Charger RC, Tapered, DebonAir+, 15x110mm axle, 130mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7120, Hollowtech II, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

WHEELS

WHEELSET FRONT	DT Swiss M 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss M 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TYRE REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	125	125	150	150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country