

# XF 9.2 DC

Matte Mustard

MTB FULL-SUSPENSION / XF TR



COMPUTER VISUALIZATION

## SPECIFICATION

### ISO AND ASTM NORM

|           |                                                                 |
|-----------|-----------------------------------------------------------------|
| ISO norm  | ISO 4210-2 MTB bicycles                                         |
| ASTM norm | ASTM 3 For rough Off-Road riding and jumps less than 61cm (24") |

### FRAMESET

|                 |                                                                                                                                                                                                              |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FRAME           | Carbon MTB Trail SU-01, Advanced Trail Geometry, Travel 130 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost 12x148 mm, Inner Cable Routing, dropper seat post ready |
| SUSPENSION FORK | RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 130mm travel                                                                                                                                         |
| REAR SHOCK      | AF2 - Twin, LockOut Lever, size 190x51mm                                                                                                                                                                     |
| BOTTOM BRACKET  | SHIMANO BB-MT500PA, PressFit, shell 41x92mm                                                                                                                                                                  |
| HEADSET         | ACROS AZX-220 R4, ZS44/28.6 - ZS56/40, BlockLock 150°                                                                                                                                                        |
| REAR AXLE       | SB01, TA12x171.5, M12xP1.5x15.5L, Black                                                                                                                                                                      |

### DRIVETRAIN

|                 |                                                     |
|-----------------|-----------------------------------------------------|
| SHIFTERS RIGHT  | SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed |
| REAR DERAILLEUR | SHIMANO DEORE RD-M6100, Shadow Plus Design          |
| CRANKSET        | SHIMANO FC-MT510, 34T                               |
| CASSETTE        | SHIMANO DEORE CS-M6100, 12-speed, 10-51T            |
| CHAIN           | SHIMANO DEORE CN-M6100                              |

### BRAKING SYSTEM

|             |                                               |
|-------------|-----------------------------------------------|
| BRAKE FRONT | SHIMANO MT420, 4 piston, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT54, 180mm                        |
| BRAKE REAR  | SHIMANO MT420, 4 piston, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT54, 180mm                        |

### WHEELS

|            |                                                          |
|------------|----------------------------------------------------------|
| HUB FRONT  | SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE |
| RIM FRONT  | WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready       |
| TYRE FRONT | Schwalbe Wicked Will Performance, 29x2.40", ADDIX        |
| HUB REAR   | SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE |
| RIM REAR   | WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready       |
| TYRE REAR  | Schwalbe Wicked Will Performance, 29x2.40", ADDIX        |
| SPOKES     | SAPIM Leader, Stainless Black                            |
| NIPPLES    | SAPIM, Alloy                                             |

### COCKPIT

|             |                                   |
|-------------|-----------------------------------|
| STEM        | ONE ICR, Alloy, 35mm, 0°          |
| HANDLEBAR   | ONE Alloy, 12mm rise, 760mm, 35mm |
| GRIPS LEFT  | ONE Race, Lock-On                 |
| GRIPS RIGHT | ONE Race, Lock-On                 |

### PARTS

|                 |                                       |
|-----------------|---------------------------------------|
| SADDLE          | Fizi:k Ridon X5, Alloy                |
| SEAT POST LEVER | SHIMANO SL-MT500-L, Seat post lever   |
| SEATPOST        | ONE Sport Dropper Post, Alloy, 30.9mm |
| SEAT POST CLAMP | ONE CC-080A, 34.9mm, Black            |

## GEOMETRY

| FRAME SIZE                     | 15.5" (S) | 17.5" (M) | 19.0" (L) | 21.0" (XL) |
|--------------------------------|-----------|-----------|-----------|------------|
| WHEEL SIZE                     | 29        | 29        | 29        | 29         |
| BB DROP (MM)                   | 29        | 29        | 29        | 29         |
| SEAT TUBE LENGTH (MM)          | 393       | 431       | 482       | 533        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 584       | 610       | 630       | 650        |
| STACK HEIGHT (MM)              | 589       | 600       | 608       | 617        |
| REACH (MM)                     | 407       | 429       | 449       | 465        |
| SEAT TUBE ANGLE                | 74°       | 74°       | 74°       | 74°        |
| HEAD TUBE ANGLE                | 66°       | 66°       | 66°       | 66°        |
| REAR CENTER (MM)               | 428       | 428       | 428       | 428        |
| HEAD TUBE LENGTH (MM)          | 90        | 100       | 110       | 120        |
| WHEELBASE (MM)                 | 1154      | 1180      | 1200      | 1220       |
| STEM (MM)                      | 35        | 50        | 50        | 50         |
| HANDLEBAR (MM)                 | 760       | 760       | 760       | 760        |
| CRANKSET (MM)                  | 170       | 175       | 175       | 175        |
| SEATPOST (MM)                  | 125       | 125       | 150       | 150        |

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification.<br/>For availability and prices, please contact the retailers in your city/country

superior.