

XF 6.6 DC

Matte Green Grey

MTB FULL-SUSPENSION / XF TR



SPECIFICATION

ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

FRAMESET

FRAME	Alu X6 Ultimate MTB Trail SU-02.2, Advanced Geometry Travel 130 mm, Integrated Cable Routing, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready.
SUSPENSION FORK	RockShox PIKE Select Charger RC, Tapered, DebonAir+, 15x110mm axle, 130mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7120, Hollowtech II, 34T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TYRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	368	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	125	125	150	150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country