

iXR 6.5

Matte Green Grey

iGRAVEL | Light / iXR



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote, Drop Bar

FRAMESET

FRAME	SU-E50-01, Alloy double-buttred , Gravel Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Bike packing and mudguards ready
SUSPENSION FORK	RockShox RUDY Base, Tapered, SoloAir, 12x100mm axle, 40mm travel
HEADSET	ACROS AZX-1306S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02, TA12x165, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 160mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 160mm

WHEELS

WHEELSET FRONT	DT Swiss HG 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss HG 1800 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX
TIRE REAR	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal Flex
SEATPOST	ONE Sport, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-617, 34.9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	470mm (XS)	490mm (S)	510mm (M)	530mm (L)	550mm (XL)
BB DROP (MM)	70	70	70	70	70
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	530	540	550	570	590
STACK HEIGHT (MM)	553	564	574	595	616
REACH (MM)	377	378	380	394	402
SEAT TUBE ANGLE	74,5°	74°	73,5°	73,5°	73°
HEAD TUBE ANGLE	70°	70,5°	70,5°	71°	71,5°
REAR CENTER (MM)	445	445	445	445	445
HEAD TUBE LENGTH (MM)	110	120	130	150	170
WHEELBASE (MM)	1039	1040	1045	1045	1070
STEM (MM)	80	80	90	100	110
HANDLEBAR (MM)	410	410	410	430	430
CRANKSET (MM)	165	165	170	170	170
SEATPOST (MM)	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country