

eWAY 6.4

Matte Black

eCITY / eWAY



COMPUTER VISUALIZATION

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN 17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes)

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Purion 200

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, 1-1/8", QR Type, 50mm travel
HEADSET	ONE PT-1866A-078-2 1-1/8", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE, 44T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-41T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J19DC, Disc, 36H
TIRE FRONT	SCALATO MONDANO, 50-622, Reflective Tape
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J19DC, Disc, 36H
TIRE REAR	SCALATO MONDANO, 50-622, Reflective Tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 38mm rise, 31.8mm
GRIPS LEFT	HERRMANS Line DD36
GRIPS RIGHT	HERRMANS Line DD36

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE Sport, Alloy, 30.9mm
SEATPOST CLAMP	ONE FR-E04_01, 34.9mm, Black
PEDALS	Marwi SP-823

CITY/ SUV SET

FRONT LIGHT	Spanninga X&O, 30
REAR LIGHT	Spanninga Pling XE
FENDER	Alloy
CARRIER	Alloy Carrier with MIK system

GEOMETRY

FRAME SIZE	460mm (S)	500mm (M)	540mm (L)	580mm (XL)
BB DROP (MM)	62	62	62	62
SEAT TUBE LENGTH (MM)	460	500	540	580
EFFECTIVE TOP TUBE LENGTH (MM)	580	600	620	640
STACK HEIGHT (MM)	604	626	648	670
REACH (MM)	390	397	403	409
SEAT TUBE ANGLE	72,5°	72°	71,5°	71°
HEAD TUBE ANGLE	69°	69,8°	70,5°	71,2°
REAR CENTER (MM)	485	485	485	485
HEAD TUBE LENGTH (MM)	170	180	190	200
WHEELBASE (MM)	1127	1133	1139	1145
STEM (MM)	90	90	110	110
HANDLEBAR (MM)	620	620	620	620
CRANKSET (MM)	170	170	170	170
SEATPOST (MM)	300	300	300	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.